

Large Synoptic Survey Telescope (LSST) Data Management

Characterization Metric Report: Science Pipelines Version 18.0.0


G. Comoretto on behalf of Science Pipelines Team

DMTR-141

Latest Revision: 2019-07-09

Abstract


This brief report describes measurements of interest that were carried out for release v18.0.0 of the Science Pipeline. The report for the previous version can be found in DMTR-131.



DMTR-141

Change Record

Version	Date	Description	Owner name
	2019-06-28	First Draft	G. Comoretto
1.0	2019-07-09	Document Issued	G. Comoretto




DMTR-141

Contents

1	Photometric Performance	2
2	Astrometric Performance	2
3	Ellipticity Correlations	3
4	Computational Performance	4
A	References	5
В	Acronyms	5





Metrics were measured using validation_data_hsc, which consists of 8 HSC engineering images: 2 *r*-band, 4 *i*'-band, and 2 *y*-band. Measurements were made on individual, separatelyprocessed, single-frame images: jointcal was not run. For comparison, we provide the SRD required "design" value of each metric as defined in the Science Requirements Document [LPM-17], and, where available, the target for this release as defined in the Data Management Development Milestone Roadmap [LDM-240]. All values were computed using the examples/runHscTest.sh script in the validate_drp package. For context, the SRD does not place any constraints on *y*-band for these KPMs. For the photometric metrics, there are only specifications for *g*, *r*, and *i*'. In the case of the ellipticity correlation metrics, there are specs only for *r* and *i*'. The *y*-band measurements are for interest and historical tracking.


Some KPMs (AF1, AD1) involve thresholds that are different for "design", "minimum", and "stretch" specifications. Thus comparing one of these metrics against a given target number is a two-level process. Both the threshold used in the calculation is dependent on the specifications, and the requirement on the computed number is dependent on the specifications.

The metrics in this report have all been computed relative to the "design" thresholds. The values of these KPMs would be different if computed against different thresholds.

Note also that the photometric performance of the pipelines in the *y*-band is an under estimate of expected delivered performance. For these tests, the *y*-band data was calibrated with *z*-band photometry. This is due to the lack of a reference catalog containing *y*-band information at this time. We recognize that the bandpass mismatch is certainly not the only source of scatter in the *y*-band photometry. These metric measurements are still worth noting in this report as a historical benchmark to track relative performance.

The *i*-band measurement of TE1 changed somewhat since the previous characterization report. The new value does not push the TE1 measurement above the "design" threshold for that KPM.

The per cycle target numbers come from the "KPMs" sheet of LDM-240.



DMTR-141

1 Photometric Performance


Submitted by Simon Krughoff and Michael Wood-Vasey

procCalRep corresponds to requirement OSS-REQ-0275 (defined in LSE-30). All other photometric performance metrics follow LSS-REQ-0093 (LSE-29) and LPM-17 table 14.

		SRD			
Metric	Unit	Requirement–	Release 19	Value	Comments
	Unit	Design	Target	value	Comments
procCalRep	mmag	<i>≤</i> 3.0	4.0	—	Need
					simulations
PA1: <i>u</i>	mmag	≤ 7.5	8.0	—	No data
PA1: g	mmag	≤ 5.0	6.0	_	No data
PA1: <i>r</i>	mmag	≤ 5	6.0	≤ 14.3	
PA1: <i>i</i>	mmag	≤ 5	5.0	12.2	
PA1: <i>z</i>	mmag	≤ 7.5	8.0	_	No data
PA1: <i>y</i>	mmag	≤ 7.5	8.0	25.40	
PF1: <i>u</i>	%	≤ 20	—	_	No data
PF1: g	%	≤ 20	—	—	No data
PF1: <i>r</i>	%	≤ 10	10.0	30.80	
PF1: <i>i</i>	%	≤ 10	10.0	27.20	
PF1: <i>z</i>	%	≤ 20	_	_	No data
PF1: <i>y</i>	%	<i>≤</i> 10	10.0	38.40	
PA2: <i>u</i>	mmag	≤ 22.5	_	_	No data
PA2: g	mmag	≤ 15	_	_	No data
PA2: <i>r</i>	mmag	≤ 15	20.0	27.20	
PA2: <i>i</i>	mmag	≤ 15	20.0	25.90	
PA2: <i>z</i>	mmag	≤ 22.5	_	_	No data
PA2: <i>y</i>	mmag	≤ 22.5	≤ 22.5	45.00	

2 Astrometric Performance

Submitted by Simon Krughoff and Michael Wood-Vasey



DMTR-141

Metric	Unit	SRD	Release 19 Target	Value
WEUTC	Onit		Release 19 Talget	value
		Requirement–		
		Design		
AM1: <i>r</i>	mas	≤ 10	20.0	3.65
AM1: <i>i</i>	mas	≤ 10	20.0	7.32
AM1: <i>y</i>	mas	<u>≤</u> 10	20.0	5.81
AF1: <i>r</i>	%	≤ 10	10.0	0.177
AF1: <i>i</i>	%	<u>≤</u> 10	10.0	0.569
AF1: <i>y</i>	%	<u>≤</u> 10	10.0	0.647
AD1: <i>r</i>	mas	≤ 20	20.0	5.75
AD1: <i>i</i>	mas	≤ 20	20.0	8.22
AD1: <i>y</i>	mas	≤ 20	20.0	8.87
AM2: <i>r</i>	mas	≤ 10	20.0	3.74
AM2: <i>i</i>	mas	<u>≤</u> 10	20.0	7.6
AM2: <i>y</i>	mas	<u>≤</u> 10	20.0	6.42
AF2: <i>r</i>	%	<u>≤</u> 10	10.0	0.162
AF2: <i>i</i>	%	<u>≤</u> 10	10.0	0.583
AF2: <i>y</i>	%	<u>≤</u> 10	10.0	1
AD2: <i>r</i>	mas	≤ 20	20.0	5.95
AD2: <i>i</i>	mas	≤ 20	20.0	8.07
AD2: <i>y</i>	mas	≤ 20	20.0	9.78


The following metrics are defined following LSR-REQ-0094 [LSE-29] and LPM-17 table 18.

3 Ellipticity Correlations

Submitted by Simon Krughoff and Michael Wood-Vasey

The following metrics are defined following LSR-REQ-0097 [LSE-29] and LPM-17 table 27.


		SRD		
Metric	Unit	Requirement-Design	Release 19 Target	Value
TE1: <i>r</i>	_	$\leq 2 \times 10^{-5}$	$\leq 3 \times 10^{-5}$	1.36×10^{-5}
TE1: <i>i</i>	_	$\leq 2 \times 10^{-5}$	$\leq 3 \times 10^{-5}$	3.16×10^{-6}
TE1: <i>y</i>	—	$\leq 2 \times 10^{-5}$	$\leq 3 \times 10^{-5}$	2.39×10^{-4}



		V18.0.0 Characterization Report	DMTR-141	Latest Revision 2019-07-09
		SRD		
Metric	Unit	Requirement–Design	Release 19 Target	Value
TE2: <i>r</i>	_	$\leq 1 \times 10^{-7}$	$\leq 3 \times 10^{-7}$	3.4×10^{-7}
TE2: <i>i</i>	_	$\leq 1 \times 10^{-7}$	$\leq 3 \times 10^{-7}$	5.32×10^{-7}
TE2: <i>y</i>		$\leq 1 \times 10^{-7}$	$\leq 3 \times 10^{-7}$	2.66×10^{-6}

4 Computational Performance

Computational performance metrics were not re-measured for this release. We expect no significant changes relative to the report on version 12 [DMTR-15].



DMTR-141

A References

- [1] [LSE-29], Claver, C.F., The LSST Systems Engineering Integrated Project Team, 2017, LSST System Requirements (LSR), LSE-29, URL https://ls.st/LSE-29
- [2] **[LSE-30]**, Claver, C.F., The LSST Systems Engineering Integrated Project Team, 2018, *Observatory System Specifications (OSS)*, LSE-30, URL https://ls.st/LSE-30
- [3] **[LPM-17]**, Ivezić, Ž., The LSST Science Collaboration, 2018, *LSST Science Requirements Doc-ument*, LPM-17, URL https://ls.st/LPM-17
- [4] **[LDM-240]**, Kantor, J., Jurić, M., Lim, K.T., 2016, *Data Management Releases*, LDM-240, URL https://ls.st/LDM-240
- [5] **[DMTR-131]**, Krughoff, S., Wood-Vasey, M., 2019, *Characterization Metric Report: Science Pipelines Version 17.0*, DMTR-131, URL 1s.st/DMTR-131
- [6] **[DMTR-15]**, Wood-Vasey, M., Swinbank, J., 2017, *Characterization Metric Report: Science Pipelines Version 13.0*, DMTR-15, URL https://ls.st/DMTR-15

B Acronyms

Acronym Description